OSPRACHT® HEAR. BE HEARD.

Aura Professional UC™Conference Phone

Desktop PTSN and Softphone for PC/Mac via USB



A CONFERENCING PHONE WITH ALL YOU NEED

Connect it to your landline (PSTN) for standard conferencing, or as a Softphone with your PC/Mac via USB. You can even add in external mics, a power amplifier, or mixing console using the auxiliary audio ports.

The Aura Professional UC™ has everything you need to sound professional, without the high price tag. It lets you conference using a range of devices making it a versatile and flexible choice.

MSRP:	\$399.99	
UPC	800807300484	
Part#	CP-3012	

AURA PROFESSIONAL UC™ FEATURES

Ol Compatibility: Analog PSTN line and Softphone for PC/Mac using USB.

O2 Call mute, call hold, three-way calling in all modes.

03 Wide-band acoustic echo cancellation with HD voice, dynamic noise suppression, automatic gain control, voice band equalization and intelligent

04 Make Skype and other VoIP app conference calls using your PC/Mac.

05 PSTN direct dial, redial, rapid dial, recall, second flash.

06 Switch from analog phone calls to USB VoIP calls








Aura Professional UC™ Conference Phone

Desktop PTSN and Softphone via USB for PC/Mac



- Microphone Mute
- Call Hold
- Standard keypad
- 4 Redial and Flash buttons
- Green and Red microphone indicator LEDs
- OK (Accept) button
- Menu
- Caller ID
- Ring volume adjust
- Volume up/down switches



Package Includes

- **O**Conference Phone
- 2Audio Transfer Adapter
- **OUSB** Cable
- 4AC adapter
- **G**RJ-11 Cable
- **5**Line In/Line Out Cable
- **6**Power Extension Cable
- **O**Users Guide (not shown)

Optional, sold separately External Microphone Microphone Cable



Specifications

FEATURES

- •Wide-band acoustic echo cancellation with HD voice, dynamic noise suppression, automatic gain control, voice band equalization and intelligent microphone mixing.
- •Four Internal uni-directional microphones.
- •USB VoIP, suitable for PC/Mac, Video systems, UC communications.
- •Built in 4-way conferencing.
- •Auxillary port allows external devices to connect.
- ·Speaker volume up to 90dB.

AUDIO SPECIFICATIONS

DSP based deep echo cancellation: -65dB

Echo Tail: 500ms

Bi-directional Noise Suppression: -18dB

LEC: - 25 dB, length 32ms

USB VolP

ELECTRICAL SPECIFICATIONS

USB Connector: Standard B type

Voice frequency response: 100Hz - 16kHz

TELEPHONE SPECIFICATIONS

Telephone Connection: Analog PBX or standard analog

PSTN line

Telephone Connector: Standard RJ-11 Audio Frequency Band: 200Hz - 3400Hz

Certifications: FCC part 15 Class A, A-Tick, Canadian,

UL. VCCI. RoHS

MECHANICAL SPECIFICATIONS

Dimensions Phone: 13.3"L x 2.5"H (33.8 x 6.3)cm

Weight: 1lb 10oz (740g)

Package: 14" x 14" x 4" (35.5 x 35.5 x 10.2)cm

Package weight: 4lb (1.9kg)

Operating Temperature: 32° - 122°F (0 - 50)°C

COMPATIBILITY

